



PREASSIGNED PRODUCTION # 098447.00

NOTES:

1. MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
2. MAXIMUM PILOT ECCENTRICITY .004 T.I.R
3. PERMISSIBLE SHAFT RUNOUT .002 T.I.R.
4. GASKETS THROUGHOUT.

NO.		REVISION		BY & DATE	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH THE CONTRACT UNDER WHICH IT WAS PREPARED. ANY REPRODUCTION OR TRANSMISSION OF THIS DRAWING IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF LEESON ELECTRIC COMPANY IS PROHIBITED.					
UNL	DESIGNED	DEC	INCHES	±.1	TITLE
X		X	±.03		42 FRAME DC
XXX	±.005				
XXXX	±.0005				
CHK	ANG	±1/2"			
RPP	DIST				
LEESON ELECTRIC MOTORS GEARMOTORS AND DRIVES			DRAWN: SAO 10/6/09		
CAD FILE: 1320UTLINE-09			CHK:		
SIZE: DRAWING NO. B 1320UTLINE-09			APPD:		
			SCALE: 5=8		
			REF: QUPRO0278		
			FIN:		
			PREV:		