



PREASSIGNED PRODUCTION # 098442.00

NOTES:

1. MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
2. MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
3. PERMISSIBLE SHAFT RUNOUT .002 T.I.R.
4. GASKETS THROUGHOUT.

NO.		REVISION		BY & DATE	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH THE CONTRACT UNDER WHICH IT WAS PREPARED. IT IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT.		UNLESS SPECIFIED		DEC.	
		INCHES		±.1	
		XX		±.03	
		XXX		±.005	
		XXXX		±.0006	
		MATL		FINISH	
CAD FILE		1270UTLINE-09		SIZE	
RPP		ANG		DRAWING NO.	
DIST		±1/2"		B 1270UTLINE-09	
				REV.	
				DRAWN	
				SAO 10/6/09	
				CHK	
				APPD	
				SCALE	
				5=8	
				REF	
				QUPR027Z	
				FNF	
				PREV	



ELECTRIC MOTORS
GEARMOTORS
AND DRIVES

OUTLINE
42 FRAME DC